

Model:GT-85-14

Size

Length: 84.8mm

Width: 69.2mm

Height: 26.25mm





Angle: $75^{\circ} \times 135^{\circ}$

Edge thickness: 3.5mm


Material: Borosilicate glass

Brief Introduction:

This product is used for the street lighting and other purpose with the 50W~150W integrated chip



>Product Detail



>More Features

STREETLIGHT PHOTOMETRIC TEST REPORT

Test:U:34.77V I:0.8459A P:29.41W PF:1.000 Freq:0Hz Lamp Flux:4960.77x1 lm		
NAME: 85-14-046(2018.8.24)	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 167.86 lm/W
MODEL	046	I _{max} (cd)	2349	S/MH (C0/180)	1.89	
NOMINAL POWER(W)	29	LOR (%)	99.5	S/MH (C90/270)	0.93	
RATED VOLTAGE(V)	34	TOTAL FLUX(lm)	4937.2	η UP,DN (C0-180)	0.0,47.0	
NOMINAL FLUX(lm)	4960.77	CIE CLASS	DIRECT	η UP,DN (C180-360)	0.0,52.5	
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	50	η down (%)	99.5	CIBSE SHR MAX	1.30	

